

BEST AVAILABLE COPY

Serial No. 10/606,257

IN THE CLAIMS:

Please amend the claims as shown in the following claim listing. The claim listing replaces all prior claim versions and claim listings in the application.

1. (Currently Amended) Apparatus comprising:

a modular headliner assembly for a vehicle having a side structure and a roof, said headliner assembly comprising:

a headliner;

an inflatable vehicle occupant protection device inflatable away from the vehicle roof into a position between the side structure of the vehicle and a vehicle occupant;

a fill tube having a portion located in said inflatable vehicle occupant protection device;

a support device having a portion ~~adapted to clamp~~ that clamps around a portion of said fill tube ~~to connect and connects~~ said fill tube and said inflatable vehicle occupant protection device to said support device; and

a grab handle having a portion that extends ~~extendable~~ through said headliner and into said support device, said grab handle being ~~adapted to~~ releasably ~~interconnect~~ interconnected with said support ~~device, device~~ to connect said grab handle ~~and~~ holding said headliner connected with said support device and said grab handle being releasable to enable removal of said headliner from said support device and said vehicle occupant restraint to said headliner;

BEST AVAILABLE COPY

Serial No. 10/606,257

a first connector that connects ~~for connecting~~ said support device to the vehicle and initially connects ~~to initially connect~~ said modular headliner assembly to the vehicle; and

a second connector that extends ~~extendable~~ through said support device and said grab handle and fixedly connects ~~to fixedly connect~~ said modular headliner assembly to the vehicle.

2. (Original) Apparatus as recited in claim 1, wherein said first connector comprises a push-in connector and said second connector comprises a threaded fastener.

3. (Original) Apparatus as recited in claim 2, wherein said push-in connector is formed together with said support device as a single piece of molded plastic.

4. (Currently Amended) Apparatus comprising:

a modular headliner assembly for a vehicle having a side structure and a roof, said headliner assembly comprising:

a headliner;

an inflatable vehicle occupant protection device
inflatable away from the vehicle roof into a position between the side structure of the vehicle and a vehicle occupant;

a fill tube having a portion located in said inflatable vehicle occupant protection device;

a support device having a portion adapted to clamp around a portion of said fill tube to connect said fill tube

BEST AVAILABLE COPY

Serial No. 10/606,257

and said inflatable vehicle occupant protection device to said support device; and

a grab handle having a portion extendable through said headliner and into said support device, said grab handle being adapted to releasably interconnect with said support device to connect said grab handle and said support device to said headliner;

a first connector for connecting said support device to the vehicle to initially connect said modular headliner assembly to the vehicle;

a second connector extendable through said support device and said grab handle to fixedly connect said modular headliner assembly to the vehicle; and

~~Apparatus as defined in claim 1,~~ wherein said portion of said grab handle comprises an anchor portion insertable into a fastener receiving portion of said support device, said anchor portion including at least one latch portion that engages said support device to connect said grab handle to said support device.

5. (Original) Apparatus as defined in claim 4, wherein said latch portion of said anchor portion extends around a dentation extending from a surface of said fastener receiving portion, said latch portion including a surface that engages said dentation to connect said grab handle to said support device.

BEST AVAILABLE COPY

Serial No. 10/606,257

6. (Previously Presented) Apparatus as defined in claim 4, wherein said grab handle has a first end and an opposite second end, an anchor portion extending from each of said first and second ends of said grab handle in a first direction, parallel to each other.

7. (Original) Apparatus as defined in claim 6, wherein said anchor portion extending from said first end of said grab handle is insertable into a first support device and said anchor portion extending from said second end of said grab handle is insertable into a second support device.

8. (Previously Presented) Apparatus as defined in claim 1, wherein said inflatable vehicle occupant protection device and said fill tube, when connected to the vehicle, extend along an intersection of the side structure of the vehicle and the vehicle roof.

9. (Original) Apparatus as defined in claim 1, further comprising an inflation fluid source that provides inflation fluid for inflating said inflatable vehicle occupant protection device.

10. (Original) Apparatus as defined in claim 9, wherein said inflatable vehicle occupant protection device is an inflatable curtain having a stored position extending along the side structure adjacent a roof of the vehicle, said inflatable curtain being inflated away from the vehicle roof

BEST AVAILABLE COPY

Serial No. 10/606,257

into said position between the side structure of the vehicle and a vehicle occupant.

11. (Original) Apparatus as defined in claim 10, wherein said inflation fluid source is in fluid communication with said fill tube, said inflation fluid source, when actuated, providing inflation fluid to said fill tube, said fill tube directing said inflation fluid into said inflatable curtain to inflate said inflatable curtain.

12. (Original) Apparatus as defined in claim 10, wherein said inflatable curtain, when inflated, extends along the side structure of the vehicle between an A pillar and a C pillar of the vehicle.

13. (Original) Apparatus as defined in claim 10, wherein said inflatable curtain, when inflated, overlies at least a portion of an A pillar, a B pillar and a C pillar of the vehicle.

14. (Original) Apparatus as defined in claim 10, further comprising a sensor for sensing a vehicle condition for which deployment of said inflatable curtain is desired, said sensor actuating said inflation fluid source to provide inflation fluid to inflate said inflatable curtain.

BEST AVAILABLE COPY

Serial No. 10/606,257

15. (Original) Apparatus as defined in claim 10, wherein said inflation fluid source comprises an inflator that is actuatable to inflate said inflatable curtain.

16. (Currently Amended) An apparatus for helping to protect an occupant of a vehicle having a side structure and a roof, said apparatus comprising:

a headliner;

an inflatable vehicle occupant protection device inflatable away from the vehicle roof into a position between the side structure of the vehicle and the vehicle occupant;

a fill tube having a portion located in said inflatable vehicle occupant protection device;

a support device having a portion that clamps around a portion of said fill tube;

a grab handle having a portion adapted to extend that extends through said headliner and ~~interconnect~~ interconnects with said support device, ~~support device to~~ connect said grab handle holding said headliner connected with said support device and said grab handle being releasable to enable removal of said headliner from said support device and said vehicle occupant restraint ~~said headliner, said grab~~ handle, and said support device with each other; and

a fastener ~~extendable~~ that extends through said grab handle and said support device ~~to connect~~ and connects said grab handle, said support device, said headliner, said fill tube, and said inflatable vehicle occupant protection device to the vehicle.

BEST AVAILABLE COPY

Serial No. 10/606,257

17. (Currently Amended) A headliner assembly for a vehicle, said headliner assembly comprising:

a headliner;

an inflatable side curtain;

a fill tube for delivering inflation fluid to said side curtain;

a support device having a portion ~~adapted to clamp~~ that clamps around a portion of said fill tube to connect said fill tube and said side curtain to said support device; and

a grab handle having a portion ~~extendable~~ that extends through said headliner and into said support device, said grab handle being ~~adapted to releasably interconnect~~ interconnected with said support ~~device, device to connect~~ said grab handle and holding said headliner connected with said support device and said grab handle being releasable to enable removal of said headliner from said support device and said vehicle occupant restraint to said headliner;

a first connector that connects ~~for connecting~~ said support device to the vehicle and initially connects to ~~initially connect~~ said support device, said grab handle, said headliner, said fill tube, and said side curtain to the vehicle; and

a second connector that extends ~~extendable~~ through said support device and said grab handle and fixedly connects ~~to fixedly connect~~ said support device, said grab handle, said headliner, said fill tube and said side curtain to the vehicle.

BEST AVAILABLE COPY

Serial No. 10/606,257

18. (Currently Amended) Apparatus for a vehicle, said apparatus comprising:

a headliner, an inflatable side curtain, and a grab handle assembled together as a module;

a push-in connector for initially connecting said module to the vehicle; and

a threaded connector that extends extendable through said grab handle and fixedly connects ~~to fixedly connect~~ said module to the vehicle, said threaded connector and said grab handle being ~~removable to release removed~~ such that said headliner releases from the vehicle, said push-in connector maintaining said side curtain connected to the vehicle.

19. (Previously Presented) Apparatus comprising:

a modular headliner assembly for a vehicle having a side structure and a roof, said headliner assembly comprising:

a headliner;

an inflatable vehicle occupant protection device inflatable away from the vehicle roof into a position between the side structure of the vehicle and ~~the~~ a vehicle occupant;

a fill tube having a portion located in said inflatable vehicle occupant protection device;

a support device having a portion adapted to clamp around a portion of said fill tube to connect said fill tube and said inflatable vehicle occupant protection device to said support device; and

a grab handle having an anchor portion extendable through said headliner and into a fastener receiving portion

BEST AVAILABLE COPY

Serial No. 10/606,257

of said support device, said anchor portion including at least one latch portion that engages said support device to releasably connect said grab handle and said support device to said headliner;

a first connector for connecting said support device to the vehicle to initially connect said modular headliner assembly to the vehicle; and

a second connector extendable through said support device and said grab handle to fixedly connect said modular headliner assembly to the vehicle.

20. (New) Apparatus as defined in claim 1, wherein said support device removably clamps to said portion of said fill tube.

21. (New) Apparatus as defined in claim 20, wherein said support device includes first and second clamp flanges, said first and second clamp flanges being spaced apart in an open position allowing removal of said support device from said portion of said fill tube, said first and second clamp flanges engaging each other in a closed position securing said support device to said portion of said fill tube.

22. (New) Apparatus as defined in claim 1, wherein said first and second connectors are parallel to each other.